

# M.A.S.A. EXTRUDECK CANOPY HANGER-ROD SPAN CHART



CLIENT

Drawn by: P. SORVILLO  
 REV. By: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Description: \_\_\_\_\_

PROJECT  
 HANGER-ROD EXTRUDECK  
 SPAN INFORMATION

PROJECTION	HANGER-ROD SPACING	TOTAL HANGER-ROD LENGTH AT 45°
24" (MIN)	(72" STANDARD O.C.) NOTE: HANGER-ROD SPACING GREATER THAN OR LESS THAN CAN BE ACHIEVED.	14.5"
30"		22.5"
36"		31.5"
42"		40"
48"		48.5"
54"		56.5"
60"		65"
66"		74"
72"		82"
78"		91"
84"		99"
90"		107.5"
96" (MAX)		116"

CENTER-ON-CENTER SPAN BETWEEN HANGER-ROD ARE SET STANDARD AT 72" (6'-0")  
 CANOPY STANDARDS ARE 406" (29'-0")  
 PRODUCT OUTSIDE STANDARD PARAMETERS ARE SUBJECT TO SITE SPECIFIC ENGINEERING.

HANGER-ROD ANGLES 21° TO (45° STANDARD)  
 ANGLES GREATER THAN 45° CAN BE PROVIDED.  
 "CONSIDER BRYN-MAWR CANTILEVER CONNECTION" FOR ANGLES LESS THAN 21°

ALUMINUM T-BAR ADJUSTABLE HANGER ROD ATTACHMENT SUPPORT

12" TYP.

8" TYP.

"SEE FACIA AND CROWN PROFILES"  
 "SEE LIGHTING OPTIONS"  
 "SEE DRAINAGE OPTIONS"  
 "SEE OBSCURITY SCREEN OPTIONS"

